

Thank you for purchasing the DOME Motion Detector, which works with your Z-Wave Certified Controller to monitor areas of your home for movement and ambient light levels.



Figure 1 - Motion Detector Front

Including/Connecting into the Z-Wave Network: Follow the instructions for your Z-Wave certified Controller to enter inclusion mode. When prompted by the Controller:

- When prompted by the Controller:
 1. For proper inclusion, bring the Motion Detector to within 10 feet of your Controller. After inclusion, the device can be moved to any desired location.
 2. Remove the cover of the Motion Detector by twisting it part.
 3. Remove the Battery Tab.
- 4. Press the Connect Button quickly 3 times in The LED Indicator will flash five times indicating

inclusion





Excluding/Disconnecting from the Z-Wave Network

Control of the instructions for your 2-Wave certified Controller follow the instructions for your 2-Wave certified Controller to enter exclusion mode. When prompted by the Controller. Remove the Cover and make sure the Motion Detector is powered. Press the Connect Button quickly 3 times in a row.

The LED Indicator will flash five times indicating exclusion/ disconnection.

To disconnect from the Z-Wave Network and restore factory default settings:

- You can use the facets on the Sensor Body to properly angle the Motion Detector on a table top or bookshelf to monitor a room. Remove the Cover and make sure the Motion Detector is powered.
 Hold the Connect Button for 10 seconds until the LED Indicator blinks once, then release the button. Remove the Magnetic Cradle and store it for later use if needed.
- Only do this if the controller is disconnected or othe able!





How to Use—Table Top:

Resetting the Motion Detector to Factory Settings:

How to Use—Wall Mount:

How to Use—wall Mount: You can nount the Motion Detector on any wall with a central line-of-sight perspective of the area you wish to monitor. See Figure 4 to visualize the Motion Detector's coverage area and its optimal positioning. It is best to mount the Motion Detector as high as possible to avoid limiting its effective range with obstacles like tables and chairs.



Installation—With Double Stick Tape:
 1. Wipe your wall clean of any dirt and grease.
 Peel-and-stick the Magnetic Cradle to your wall using the included double-stick tape.
 Interact the Sensor Body on the Magnetic Cradle at an angle to properly monitor your room, and the magnet will hold the Sensor Body in place
 Installation—With Screws:
 Twist the mount counterclockwise to separate the Magnet from the Wall Mount.
 Hold the Wall Mount.
 Reattach the Magnet to the Wall Mount
 Finder the Sensor Body on the Magnetic Cradle at an angle to properly monitor your room, and the magnet will hold the Sensor Body on the Magnet Cradle at an angle to properly monitor your room, and the magnet will hold the Sensor Body on place.

<text><text><text><text><text>

<text><text><text><text><text><text><text>

CORRECT DISPOSAL OF BATTERIES IN THIS PRODUCT This marking on the product accessories or literature indicates that the product and its electricine accessories should not be disposed of which houshafed wature to greeent possible harm to the environment or human health from uncentrolled weak disposal, places separate these terms from other types of waste and recycle them responsible promote the socialized resources. Household users should contact either the retailer where they purchased this product, or their government office, for details of where and how they can take these items for environmentally safe recvoling.

terms for exercised-analysis de receiver a la servera ad the tarty can be black because users accusate contracts that seguine a decision of the particular serveral serveral of the particular servers of the dispatch and the advectment particular tarts and with the matching measure of particular servers and server of the tarts and with the matching measure of particular servers de balances of the decision of the servers of the server of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the servers of the decision of the servers of the servers of the decision of the servers of the servers of the decision of the servers of the servers of the decision of the decision of the decision of the servers of the decision of the de

FC # Z52NAS-PD02Z

©2016 Elexa Consumer Products, Inc. 2275 Half Day Rd., Suite 333 Bannockburn, IL 60015 www.domeHA.com

